



Bay Area AQMD Regulation 8 Rule 45



VOC Less Water Less Exempt Limits for version amended 12/3/08

Coating Category	Effective 10/1/09	Effective 1/1/10	
	lbs/gal (g/L)	lbs/gal (g/L)	
Solvent (Surface Cleaner)*	.21 (25)	.21 (25)	
Pretreatment Coating	5.5 (660)	5.5 (660)	
Primer/Primer Surfacer	2.1 (250)	2.1 (250)	
Primer Sealer	2.8 (340)	2.1 (340)	
Single-Stage Coating	3.5 (420)	2.8 (340)	
Color Coating	3.5 (420)	3.5 (420)	
Underbody Coating	3.6 (430)	3.6 (430)	
Clear Coating	2.1 (250)	2.1 (250)	
Uniform Finish Coating	4.5 (540)	4.5 (540)	
Adhesion Promoter	7.0 (840)	4.5 (540)	* VOC content applies to this category only

Product Code & Name	Reducer	Hardener/ Activator	Mixing Ratio	VOC content
Solvent (Substrate Cleaner)		Limit:		0.21 lbs/gal (25 g/L)
SWX350 H2O-So-Clean Wax & Grease Remover	-	-	-	0.17 (20)
SWX360 Waterborne Pre-Cleaner	water	-	1:2	0.20 (24)
SX1005 Low VOC Wax and Grease Remover	water	-	1:1	0.21 (25)
DX394 1.4 Low VOC Cleaner*	-	-	-	1.32 (158)

*allowed only as bug & tar remover under low usage limit, see 8-45-308.5 for details

Product Code & Name	Reducer	Hardener/ Activator	Mixing Ratio	Applied VOC Less Water Less Exempt
Pretreatment Coating		Limit:		5.5 lbs/gal (660 g/L)
SX1071 Etch prime	-	SX1072	1:1	5.48 (657)
SXA1031 Etch Primer – Gray	-	-	Aerosol	N/A
Primer/Primer Surfacer		Limit:		2.1 lbs/gal (250 g/L)
DPLV 305X Acrylic Urethane Surfacer	DT18XX series	DHLV3030	4:1:1	2.03 (243)
DPLV 305X Acrylic Urethane Surfacer	-	DHLV3030	4:1	2.03 (243)
DS1002 UV Cured Primer Surfacer	-	-	Aerosol	N/A
NCP280 2.1 VOC Primer Surfacer	-	NCX285	2:1	2.1 (250)
NCP280 2.1 VOC Primer Surfacer	-	NCX285	2:1 + 10% Acetone	2.1 (250)
Primer Sealer (apply over previously coated surfaces)		Limit:		2.8 lbs/gal (340 g/L)
DSL302X Acrylic Urethane Sealer	DT18XX series	DHLV3030	3:1:1	2.80 (336)

Product Code & Name	Reducer	Hardener/ Activator	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Single-Stage Coating		Limit:		3.5 lbs/gal (420 g/L)	
CONCEPT®LV (CLV) Acrylic Urethane	DT18xx series	DCX61	DX84 or DX87	2:1+ 1 oz. DX/RTS qt +5 - 10% DT18xx Reducer	3.5 (419)
Color Coating		Limit:		3.5 lbs/gal (420 g/L)	
EHP Envirobase Waterborne Basecoat	T494	-	-	10%	3.35 (401)
EHP Envirobase Waterborne Basecoat	T494	-	-	20%	3.40 (407)
EHP Envirobase Waterborne Basecoat	T494	-	-	30%	3.50 (419)
EHP Envirobase Waterborne Basecoat	T494	T588	-	10%+10%	3.05 (366)
EHP Envirobase Waterborne Basecoat	T494	T588	-	20%+10%	3.09 (370)
EHP Envirobase Waterborne Basecoat	T494	T588	-	30%+10%	3.11 (373)
Underbody Coating		Limit:		3.6 lbs/gal (430 g/L)	
EHP Internal Repair System	T494	T581	-	100:15:15	3.08 (369)
EHP Internal Repair System	T494	T581	-	100:15:20	3.09 (370)



Bay Area AQMD Regulation 8 Rule 45



VOC Less Water Less Exempt Limits for version amended 12/3/08

Product Code & Name	Reducer	Hardener/ Activator	Additives	Mix Ratio	Applied VOC Less Water Less Exempt
Clear Coating		Limit:			2.1 lbs/gal (250 g/L)
DC3010 Deltron High Velocity Clear	-	DCH3610, DCH3620, DCH3630, DCH3640	-	4:1	2.08 (249)
DC4010 Velocity Premium Clear	-	DCH3610, DCH3620, DCH3630, DCH3640	-	4:1	2.05 (246)
DCU2010 2.1 Speed Clear	-	DCX2009, DCX2011 or DCU2012	-	4:1	2.07 (248)
DC4125 Ceramiclear Clearcoat	-	DC4126	-	2:1	2.05 (246)
Additional Products: (listing not intended to be all inclusive)					
DPX801 Universal Plastics Primer	SUA4903 Advanced Plastic Bond		SXA1044 High Build Flexible Surfacer		
SLV4985 Universal Matting Agent	SWX100 Waterborne Gun Cleaner		SXA1050 Plastic Adhesion Promoter		
SLV73 Fisheye Eliminator	SXA840 OneChoice Blending Solvent		SX1044 High Build Flexible Surfacer		
SLV814 Universal Flexibilizer	SXA1030 Black Guide Coat		SX1050 Plastic Adhesion Promoter		
SU4901 Clean and Scuff Sponge	SXA1033 Texture Spray		SXA1044 High Build Flexible Surfacer		
SU4902 Plastic Prep Wipe	SXA1041 Bumper Black		SXA1050 Plastic Adhesion Promoter		
SU4903 Advanced Plastic Bond	SXA1043 Flexible Sealer		SX1044 High Build Flexible Surfacer		
DX101 Sanding Paste					
DX310 EZ Cleaner					

This "Bay Area AQMD Rule 8-45 (PPG Deltron)" wall chart is intended to provide INFORMATION to PPG's customers. In providing this wall chart, PPG makes no separate or additional warranties, express or implied, and assumes no liability or responsibility arising out of its use. It is the responsibility of each customer, RE-SELLER AND END USER of PPG's products to independently ascertain that their practices are legal, appropriate and constitute sound product stewardship. This "Bay Area AQMD Rule 8-45 (PPG Deltron)" wall chart does not include all currently compliant Deltron products. The representative products listed are compliant with Rule 8-45 VOC limits as of the date of this wall chart; however, subsequent changes in Rule 8-45 may change the compliance status of the listed products. It is the responsibility of the end user to review and comply with current regulations, including applicable coating category VOC limits, as of the date of product purchase and/or use. This document is not INTENDED to define or create legal rights or obligations. It is the responsibility of each customer, RE-SELLER AND END USER to comply with all applicable federal, state and local laws.